


## SPECIFICATION

SIZE / TOOL		20Q5			23Q5			32Q5		
MODEL		LT-20Q5LF	LT-20Q5TF	LT-20Q5MF	LT-23Q5LFH	LT-23Q5TFH	LT-23Q5MFH	LT-32Q5LFH	LT-32Q5TFH	LT-32Q5MFH
SYSTEM	PAL/SECAM*B/G, D/K, I	•	•	—	•	•	—	•	•	—
	SECAM*LL'	•	—	—	•	—	—	•	—	—
	NTSC 3.58/4.43(AV)	•	•	•	•	•	•	•	•	•
	PAL N/M	—	—	•	—	—	•	—	—	•
PICTURE	NTSC M	—	•	•	—	•	•	—	•	•
	Progressive Scan	•	•	•	•	•	•	•	•	•
	Skin Tone	—	—	—	—	—	—	—	—	—
	Black Stretcher	—	—	—	—	—	—	•	•	•
	Digital Comb Filter	4H	4H	4H	4H	4H	4H	4H	4H	4H
	*DCTI/DLTI	•	•	•	•	•	•	•	•	•
	Picture Enhancer	—	—	—	—	—	—	—	—	—
SOUND	Picture Mode(Dynamic, Standard, Mid, Game, User)	5 Mode	5 Mode	5 Mode	5 Mode	5 Mode	5 Mode	5 Mode	5 Mode	5 Mode
	Stereo / NICAM	•/•	•/•	US/KOREA/JAPAN	•/•	•/•	US/KOREA/JAPAN	•/•	•/•	US/KOREA/JAPAN
	Sound Effect	surround	Surround	Surround	surround	Surround	Surround	Surround	Surround	Surround
	AVL(Auto Volume Leveler)	•	•	•	•	•	•	•	•	•
	Equalizer	•	•	•	•	•	•	•	•	•
	Sound Output	5W x 2	5W x 2	5W x 2	10W x 2	10W x 2	10W x 2	10W x 2	10W x 2	10W x 2
	SoundMode (Flat, Music, Movie, Speech, User)	5 Mode	5 Mode	5 Mode	5 Mode	5 Mode	5 Mode	5 Mode	5 Mode	5 Mode
TELETEXT	Page	10 page	10 page	—	10 page	10 page	—	1000 page	1000 page	—
	TOP/FLOF	•/•	•/•	—	•/•	•/•	—	•/•	•/•	—
	*WSS	•	•	—	•	•	—	•	•	—
CAPTION	Caption / Vchip	—	—	•/•	—	—	•/•	—	—	•/•
OSD	MENU/Half Tone	•	•	•	•	•	•	•	•	•
Multi Language	•	•	•	•	•	•	•	•	•	•
Program List / Edit	•/•	•/•	•/X	•/•	•/•	•/X	•/•	•/•	•/•	•/X
OTHERS	Double Window Text	•	•	—	•	•	—	—	—	—
Double Window PIP	—	—	—	—	—	—	—	—	—	—
PIP(AV/PC, RF/PC, AV/RF) / POP	—	—	—	•, X / •	•, X / •	•, X / •	•, X / •	•, X / •	•, X / •	•, X / •
Zoom Function	—	—	—	•	•	•	•	•	•	•
ARC (Aspect Ratio Control)	—	—	—	•	•	•	•	•	•	•
FM Radio	•	•	•	•	•	•	•	•	•	•
Real Clock	•	•	•	•	•	•	•	•	•	•
DIGITAL APPLICATION	HD Ready	—	—	—	•	•	•	•	•	•
DTV Tuner	—	—	—	—	—	—	—	—	—	—
INPUT	HDMI™ Input	—	—	—	—	—	—	•	•	•
DVI Input	—	—	—	DVI-D	DVI-D	DVI-D	—	—	—	—
Component 1(Y/Pb/Pr)	—	480i/576i	480i/576i	480i~1080i	480i~1080i	480i~1080i	480P~1080i	480i~1080i	480i~1080i	480i~1080i
Component 2 (Y/Pb/Pr)	—	—	—	—	480i~1080i	480i~1080i	—	480i~1080i	480i~1080i	480i~1080i
S.Video	•	•	•	•	•	•	•	•	•	•
AV 1	Full SCART	PHONE	PHONE	Full SCART	PHONE	PHONE	Full SCART	PHONE	PHONE	PHONE
AV 2	PHONE	—	—	Half SCART	—	—	Half SCART	—	—	—
AV 3	—	—	—	—	—	—	—	—	—	—
Digital Sound(optical/Coaxial)	—	—	—	—	—	—	—	—	—	—
D-SUB	—	—	—	•	•	•	•	•	•	•
PC Audio In	—	—	—	•	•	•	•	•	•	•
OUTPUT	Digital Sound(Optical/Coaxial)	—	—	—	—	—	COAX	COAX	COAX	COAX
AV Out	•	•	•	—	•	•	—	•	•	•
Woofer	—	—	—	—	—	—	—	—	—	—
Headphone	•	•	•	•	•	•	•	•	•	•
CONTROL	RS-232C	—	—	—	—	—	—	—	—	—
RJ11 or RJ45	•	•	•	•	•	•	•	•	•	•
POWER	Power(Internal / Adapter)	Adaptor(15V)			Internal(SMPs)			Internal(SMPs)		
	Power Consumption	70W below			140 W			150W		
	Stand By Power Consumption	3W below			3W below			3W below		

\*DCTI/DLTI : Digital Colour Transient Improvement

Digital Luminance Transient Improvement

\*WSS : Wide Screen Signaling





# Luxury Space with High Technology

You can enjoy the true multimedia experience with this highly advanced display technology. On the wall or on a table, its finest view can be a perfect match for your home theater system.

Also it can fit in other applications where you can feel every bit of up-to-date virtues of LCD-TV.



► LT-32Q5\*FH

- Brightness : 500 cd
- Resolution : 1366 x 768
- Response Time : 8msec
- DVB-T (Option)
- HD Ready
- Radio, Real Clock
- 1,000 TXT (EU)
- Contrast Ratio : 1000:1
- Viewing Angle : 170(H)x170(V)
- ATSC (US)



► LT-23Q5\*FH

- Brightness : 500 cd
- Contrast Ratio : 1000:1
- Resolution : 1366 x 768
- Viewing Angle : 170(H)x170(V)
- Response Time : 8msec
- HD Ready
- Radio, Real Clock



► LT-20Q5\*F

- Brightness : 450 cd
- Contrast Ratio : 500:1
- Resolution: 640 x 480
- Viewing Angle: 160(H)x140(V)
- Response Time: 16msec
- Radio, Real Clock



**Q.**